

Product Type:	Flat back Kraft Paper Tape												
Colour:	Brown												
Roll Size:	12mm to 1400mm in 50m Lengths												
Adhesive:	Rubber Natural												
Description:	A Brown coloured Kraft Paper Tape coated one side with a natural rubber resin adhesive. This product offers good adhesion to self.												
Application:	Designed for a wide range of packaging, joining, splicing and tabbing applications within the paper and cardboard industry. The product can be used for picture framing and exhibits good adhesion to a wide range of surfaces. The product provides a quick and positive seal under a wide range of temperature and humidity conditions.												
Technical Details:	<table><tr><td>Gauge :</td><td>0.17mm</td></tr><tr><td>180° Peel Adhesion:</td><td>7.6 N/cm</td></tr><tr><td>Tensile Strength:</td><td>70 N/cm</td></tr><tr><td>Elongation at Break:</td><td>3%</td></tr><tr><td>Service Temperature:</td><td>0°C to 50°C</td></tr><tr><td>Complies with:</td><td>ASTM D 6123/D 6123M-97 (2012) Type II</td></tr></table>	Gauge :	0.17mm	180° Peel Adhesion:	7.6 N/cm	Tensile Strength:	70 N/cm	Elongation at Break:	3%	Service Temperature:	0°C to 50°C	Complies with:	ASTM D 6123/D 6123M-97 (2012) Type II
Gauge :	0.17mm												
180° Peel Adhesion:	7.6 N/cm												
Tensile Strength:	70 N/cm												
Elongation at Break:	3%												
Service Temperature:	0°C to 50°C												
Complies with:	ASTM D 6123/D 6123M-97 (2012) Type II												
Surface Preparation:	The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 30°C.												
Storage:	Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.												

Order Online

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.