



Product Type:	Crepe Paper Tape – Utility Grade		
Colour:	Cream		
Roll Size:	From 6mm to 1400mm in 50m Rolls		
Adhesive:	Natural Rubber Adhesive		
Description:	A light weight beige creped paper with a soft natural rubber adhesive system, all-purpose product for non-critical applications.		
Application:	Intended for non-critical room temperature applications, such as hanging paper, poly and poster board and as a stationery tape. Also carpet seaming, silk screening, mail rooms, gold club shaft (build-up), light duty bundling, splicing, tabbing & holding		
Technical Details:	Gauge:	0.127mm	PSTC-133
	Tensile Strength:	33 N/cm	PSTC-131
	180° Peel Adhesion:	3.9 N/cm	PSTC-101
	Elongation at Break:	10%	PSTC-131
	Quick stick to Stainless Steel:	1.32 N/cm	PSTC-5
	Service Temperature:	10°C to 80°C	
Surface Preparation:	The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 30°C.		
Storage:	Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.		

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.