

Product Type: Crepe Paper Masking Tape – Industrial Grade

Colour: Cream

Roll Size: From 6mm to 1400mm in 50m rolls

Adhesive: Rubber Natural



Description: A high quality semi-bleached crepe paper with rubber based adhesive. Good conformability and tensile strength for industrial applications and low bake panel beating applications.

Application: This product is designed for many general purpose masking applications. Can be exposed to UV light up to 5 hours. Panel Beating Mask operations where a Low bake cycle is used - up to 95°C for 1 hour, plus many Industrial uses.

Technical Details:

Gauge:	0.15mm
180° Peel Adhesion:	3.9 N/cm
Tensile Strength:	37 N/cm
Service Temperature:	0°C to 95°C

Surface Preparation: The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 30°C.

Storage: Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.