

Product Type:	Single Side Butyl Cloth Tape
Colour:	Black
Roll Size:	6mm to 1200mm in 20m Lengths
Adhesive:	Butyl



Description: A black PE coated cloth with an aggressive black butyl based pressure sensitive adhesive. Developed to have an easy tear and unwind for use primarily in the building and construction industry.

- Application:**
- Forming moisture/vapour seals on membranes (construction & horticulture)
 - Patching & joining PE Sheeting and other Low Energy surfaces
 - Holding and joining as a permanent repair tape
 - Temporary hose repair

Technical Details:	Gauge:	0.35mm
	Tensile Strength:	51 N/cm
	Elongation at Break:	15%
	Adhesion to Steel:	7.4 N/cm
	Vapour Penetration:	1.0 g/m ² hrs
	Service Temperature:	-10°C to 50°C
	Storage Temperature:	15°C to 25°C
	Shelf Life:	12 Months

Surface Preparation: The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 25°C.

Storage: Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.