



| | | |
|-----------------------------|---|-----------------------|
| Product Type: | Double Sided Film - Differential Adhesive Tape | |
| Colour: | Clear | |
| Roll Size: | 6mm to 1000mm in 33m Lengths NB Special lengths available upon request | |
| Adhesive: | Acrylic Modified | |
| Description: | Clear PET Film with Permanent Acrylic adhesive on one side and removable acrylic adhesive on the other side with a white release liner. | |
| Application: | <ul style="list-style-type: none">• Holding Masking Mediums• Signage & Display• Point of Sale | |
| Technical Details: | Gauge: | 0.12mm |
| | Liner Thickness: | 0.125mm |
| | Tensile Strength: | 45 N/cm |
| | Adhesion to Steel: | Open Side: 6.8 N/cm |
| | | Closed Side: 3.4 N/cm |
| | Service Temperature: | -10°C to +110°C |
| | Storage Temperature: | 15°C to 25°C |
| | Shelf Life: | 12 Months |
| Surface Preparation: | The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 25°C. | |
| Storage: | Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place. | |
| Product Demo: | https://youtu.be/5zHe1J2m5nE https://youtu.be/yBYiT4moLtA | |

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.