



Product Type: Double Sided Clear Acrylic - White PE Liner
Temporary Mounting Tape
(See T608R for lower tack version Light Blue PE Liner)

Colour: Clear

Roll Size: 6mm to 930mm in 33m Lengths

Adhesive: Acrylic Polymer 1,000 Kg/M³ density (+/- 5%)

Description: A Clear 0.8mm solventless removable acrylic tape characterised by extreme elongation at break. It has a high density clear acrylic foam core and it is on a white PE release liner suitable for die cutting.

Application: Designed for the temporary mounting of signs and other media. The clear acrylic has a very high internal strength and so will clean remove from virtually any stable surface. Applications in the area of advertising, exhibition, display and P.O.S. particularly for rigid materials or where clarity is required.

Technical Details:

Gauge:	0.8mm
Elongation at Break:	1,600%
180° Peel adhesion:	
Stainless Steel	3.4 N/cm
ABS	2.3 N/cm
Dynamic Sheer:	
Stainless Steel	3 Kg/cm ²
ABS	2 Kg/cm ²
Static Shear:	
23°C 3.23cm ² 7 Days	500g
70°C 3.23cm ² 7 Days	250g
Service Temperature:	-30°C to +80°C (150°C Short term)
Shelf Life:	12 Months

Surface Preparation: The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 25°C.

Storage: Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.